

NEW RED CAB

- 4 uprights frame
- Platform suspended on Silent block
- "Inside the frame" door handles
- Standard heating and air conditioning system
- Openable back window
- Rear side flap for equipment cable routing
- Working LED lights



SRX	5800	6800
DISPLACEMENT / CYL. NO.	2091CC/4	2091CC/4
SUCTION	Turbo	Turbo + Intercooler
INJECTION	Common-rail	Common-rail
EMISSION REGULATION	STAGE V	STAGE V
MAXIMUM POWER	37,9 Kw 52ps @ 2600rpm	48,5Kw 66ps@ 2600rpm
MAXIMUM TORQUE	170 Nm @ 1690rpm	210Nm @ 1690rpm
TRANSMISSION	Synchronised gearbox with 32 speeds: 16 forward and 16 reverse speeds with synchronised inverter	
PTO	Rear, independent at 540/540 E, with electrohydraulic control and progressive engagement	
TRACTION	Permanent 4-wheel drive	
BRAKES	2 rear dual disc brakes acting on the 4 wheels	
HYDRAULIC SYSTEM	Standard 39 l/min Load sensing pump, opt. 55 l/min. Up to 5 double-acting distributors plus 1 oil reflow	
DRIVING POSITION	Platform suspended on Silent block. New layout of the shift levers	
MAXIMUM SPEED	30km/h	

SRX 5800/6800



The **TORA Series** was born to conceive a medium power range of professional tractors, characterised by an hydraulic, mechanical and driving comfort upgrade, in the sign of maximum efficiency with minimum waste of energy and working time.




REVERSIBLE, ARTICULATED, 4 EQUAL WHEEL DRIVE, NARROW-TRACK TRACTOR WITH **52HP/66HP** IN THE **5800/6800** VERSIONS. IT IS A COMPACT AND AGILE TRACTOR, DESIGNED FOR PROFESSIONAL USE.

STRONG POINTS

BULLBAR*

FRONT POWER LIFT*

FRONT BALLASTS*



HIGH POWER HYDRAULIC SYSTEM



ACTIO™

OPTIONAL*

Min. 980 mm
COMPACT DIMENSIONS

LOW REAR MUDGUARDS

- visibility on rear equipment, the best of the whole range
- wheels dimension: 18"

16+16 synch. inverter
TRANSMISSION

NEW REVERSIBILITY



NEW SHIFT LEVER LAYOUT

The central tunnel is now free from obstacles. The reverse shuttle and gear levers have been moved on the steering wheel's side thanks to a new technical solution, patented and unique on the market.

DIMENSIONS

SRX	5800	6800
TOTAL LENGTH	3060 mm	
MINIMUM LENGTH	980 MM WITH 210/95R18	
WHEELBASE	1460 mm	
BONNET HEIGHT	1155 mm(280/70R18), MIN. 1090 mm(29.12,5-15)	
CAB HEIGHT	2200 mm(280/70R18), MIN. 2150 mm(29.12,5-15)	
WEIGHT	ROLLBAR 1775 kg	CAB 1925 kg